

1. (Amended) An arrangement for generating and storing metering information in a meter for measuring a consumed commodity, the arrangement including:
 - a) a processing circuit operable to receive commodity consumption information and generate metering information therefrom;
 - b) a non-volatile, rewriteable random access memory for storing the metering information during normal operation, the non-volatile, rewritable random access memory operable to retain the stored metering information in the absence of ~~external~~ electrical power from a source external to the non-volatile, rewriteably random access memory.
2. (Original) The arrangement of claim 1 wherein the meter comprises an electricity meter and wherein:
 - the processing circuit is operable to generate load profiling information, said load profiling information including energy usage information for a plurality of time periods; and
 - wherein the non-volatile rewriteable random access memory is further operable to store the load profiling information.

3. (Original) The arrangement of claim 1 wherein the meter comprises an electricity meter and wherein:

the processing circuit is operable to generate metering information using one of a plurality of sets of meter formulae;

the non-volatile rewriteable random access memory is further operable to store the one of the plurality of sets of meter formulae.

4. (Original) The arrangement of claim 3 further comprising an external communication port and wherein the one of the plurality of sets of meter formulae stored in the non-volatile rewriteable random access memory may be replaced with a different one of the plurality of sets of meter formulae via communication with an external device through the external communication port.

5. (Original) The arrangement of claim 1 wherein the meter comprises an electricity meter and wherein:

the processing circuit is operable to generate metering information using a first set of calibration information; and

the non-volatile rewriteable random access memory is further operable to store the first set of calibration information.

6. (Original) The arrangement of claim 5 further comprising an external communication port and wherein the first set of calibration information may be replaced with a second set of calibration information via communication with an external device through the external communication port.

7. (Original) The arrangement of claim 1 wherein the non-volatile rewriteable random access memory is a ferromagnetic RAM.

8. (Original) The arrangement of claim 1 wherein the non-volatile rewriteable random access memory further stores at least one interim metering variable generated by the processing circuit and subsequently retrieved by the processing circuit for calculation of a metering value.

9. (Original) The arrangement of claim 1 wherein the non-volatile rewriteable random access memory further stores program code executed by the processing circuit.

10. (Original) The arrangement of claim 1 wherein:

the processing circuit is operable to generate statistical commodity consumption information, said statistical commodity consumption information including commodity usage information for a plurality of time periods; and

wherein the non-volatile rewriteable random access memory is further operable to store the statistical commodity consumption information.

11. (Original) The arrangement of claim 1 wherein the processing circuit includes plural processing devices, said plural processing devices including a digital signal processor.

CLAIMS 12 THROUGH 19 ARE CANCELLED

20. (Amended) An arrangement for generating and storing metering information in an electricity meter for measuring consumed energy, the arrangement including:

a) a processing circuit operable to receive energy consumption information and generate metering information therefrom, said metering information including load profiling information;

b) a non-volatile, rewriteable random access memory for storing the metering information during normal operation, the non-volatile, rewritable random access memory operable to retain the stored metering information in the absence of ~~external~~ electrical power from a source external to the non-volatile, rewriteable random access memory, said non-volatile, rewriteable random access memory further storing at least some program code executed by the processing circuit.

21. (Amended) An arrangement for generating and storing metering information in an electricity meter for measuring consumed energy, the arrangement including:

a) a processing circuit operable to receive energy consumption information and generate metering information using the received energy consumption information and a first set of calibration information;

Art Unit: 2829

b) a non-volatile, rewriteable random access memory for storing the first set of calibration information and for storing the metering information during normal operation, the non-volatile, rewritable random access memory operable to retain the calibration information and the stored metering information in the absence of ~~external~~ electrical power from a source external to the non-volatile, rewriteable random access memory.